

## Safety Data Sheet

Printing date 02/14/2017

Revised On 02/14/2017

## 1 Identification of the substance and manufacturer

**Trade name:** PURPLE BOUNDARY PAINT  
**Product code:** FS00057709  
**Product category:** PC9a Paints and coatings.  
**Manufacturer/Supplier:** Seymour of Sycamore  
 917 Crosby Avenue  
 Sycamore, IL 60178  
 phone: 815-895-9101  
 www.seymourpaint.com  
**Emergency telephone number:** CHEMTEL 1-800-255-3924, or 813-248-0585.

## 2 Hazard(s) identification

## Classification of the substance or mixture

Flam. Aerosol 1 H222 Extremely flammable aerosol.  
 Press. Gas H280 Contains gas under pressure; may explode if heated.  
 Acute Tox. 4 H312 Harmful in contact with skin.  
 Acute Tox. 4 H332 Harmful if inhaled.  
 Eye Irrit. 2A H319 Causes serious eye irritation.  
 STOT SE 1 H370 Causes damage to organs.  
 STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

## GHS Hazard pictograms



GHS02 GHS04 GHS07 GHS08

## Signal word

Danger

## Hazard statements

Extremely flammable aerosol.  
 Contains gas under pressure; may explode if heated.  
 Harmful in contact with skin or if inhaled.  
 Causes serious eye irritation.  
 Causes damage to organs.

## Precautionary statements

May cause respiratory irritation. May cause drowsiness or dizziness.  
 Keep away from heat/sparks/open flames/hot surfaces. No smoking.  
 Do not spray on an open flame or other ignition source.  
 Do not pierce or burn, even after use.  
 Wash hands thoroughly after handling.  
 Do not eat, drink or smoke when using this product.  
 Use only outdoors or in a well-ventilated area.  
 Wear protective gloves/protective clothing/eye protection/face protection.  
 Do not breathe dust/fume/gas/mist/vapors/spray.  
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 Call a POISON CENTER/doctor if you feel unwell.  
 IF ON SKIN: Wash with plenty of water.  
 If eye irritation persists: Get medical advice/attention.  
 Take off contaminated clothing and wash it before reuse.  
 Store locked up.  
 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.  
 Protect from sunlight. Store in a well-ventilated place.  
 Dispose of contents/container in accordance with local/regional/national/international regulations.

## 3 Composition/information on ingredients

## Chemical characterization: Mixtures

**Chemical Description:** This product is a mixture of the substances listed below with nonhazardous additions.

## Dangerous components:

74-98-6	propane	15.75%
1317-65-3	Calcium Carbonate	13.02%
67-56-1	methanol	12.7%
67-64-1	Acetone	12.68%
106-97-8	n-butane	9.25%
64742-89-8	VM&P Naphtha	7.73%
64742-47-8	Mineral Spirits	4.44%
13463-67-7	titanium dioxide	4.41%
108-65-6	PM acetate	2.79%
1330-20-7	xylene (mix)	2.52%
112926-00-8	Silicon Dioxide	1.22%

## 4 First-aid measures

**After inhalation:** Supply fresh air; consult doctor in case of complaints.  
**After skin contact:** Remove contaminated clothing. Wash exposed area with soap and water.  
**After eye contact:** Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.  
**After swallowing:** Rinse mouth with water. Do not induce vomiting.  
**Most important symptoms and effects:** Dizziness

(Contd. on page 2)

## Safety Data Sheet

Printing date 02/14/2017

Revised On 02/14/2017

Trade name: PURPLE BOUNDARY PAINT

(Contd. of page 1)

**Indication of any immediate medical attention needed:**

No further relevant information available.

**5 Fire-fighting measures**

**Extinguishing agents:** CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray.  
**Special hazards:** Can form explosive gas-air mixtures.  
**Protective equipment for firefighters:** A respiratory protective device may be necessary.

**6 Accidental release measures**

**Personal precautions, protective equipment and emergency procedures:** Use respiratory protective device against the effects of fumes/dust/aerosol.  
**Methods and material for containment and cleaning up:** Absorb liquid components with liquid-binding material.

**7 Handling and storage**

**Precautions for safe handling:** Use only in well ventilated areas.  
**Storage requirements:** Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up.

**8 Exposure controls/personal protection****Components with limit values that require monitoring at the workplace:****74-98-6 propane**

PEL (USA) Long-term value: 1800 mg/m<sup>3</sup>, 1000 ppm  
REL (USA) Long-term value: 1800 mg/m<sup>3</sup>, 1000 ppm  
TLV (USA) refer to Appendix F in TLVs&BEIs book; NIC-EX

**67-56-1 methanol**

PEL (USA) Long-term value: 260 mg/m<sup>3</sup>, 200 ppm  
REL (USA) Short-term value: 325 mg/m<sup>3</sup>, 250 ppm  
Long-term value: 260 mg/m<sup>3</sup>, 200 ppm  
Skin  
TLV (USA) Short-term value: 328 mg/m<sup>3</sup>, 250 ppm  
Long-term value: 262 mg/m<sup>3</sup>, 200 ppm  
Skin; BEI

**67-64-1 Acetone**

PEL (USA) Long-term value: 2400 mg/m<sup>3</sup>, 1000 ppm  
REL (USA) Long-term value: 590 mg/m<sup>3</sup>, 250 ppm  
TLV (USA) Short-term value: 1187 mg/m<sup>3</sup>, 500 ppm  
Long-term value: 594 mg/m<sup>3</sup>, 250 ppm  
BEI

**106-97-8 n-butane**

REL (USA) Long-term value: 1900 mg/m<sup>3</sup>, 800 ppm  
TLV (USA) Short-term value: (2370) mg/m<sup>3</sup>, (1000) ppm  
NIC-EX

**108-65-6 PM acetate**

WEEL (USA) Long-term value: 50 ppm

**1330-20-7 xylene (mix)**

PEL (USA) Long-term value: 435 mg/m<sup>3</sup>, 100 ppm  
REL (USA) Short-term value: 655 mg/m<sup>3</sup>, 150 ppm  
Long-term value: 435 mg/m<sup>3</sup>, 100 ppm  
TLV (USA) Short-term value: 651 mg/m<sup>3</sup>, 150 ppm  
Long-term value: 434 mg/m<sup>3</sup>, 100 ppm  
BEI

**112926-00-8 Silicon Dioxide**

PEL (USA) 20mppcf or 80mg/m<sup>3</sup> /%SiO<sub>2</sub>  
REL (USA) Long-term value: 6 mg/m<sup>3</sup>  
See Pocket Guide App. C  
TLV (USA) TLV withdrawn

**Ingredients with biological limit values:****67-56-1 methanol**

BEI (USA) 15 mg/L  
Medium: urine  
Time: end of shift  
Parameter: Methanol (background, nonspecific)

**67-64-1 Acetone**

BEI (USA) 50 mg/L  
Medium: urine  
Time: end of shift  
Parameter: Acetone (nonspecific)

(Contd. on page 3)

## Safety Data Sheet

Printing date 02/14/2017

Revised On 02/14/2017

Trade name: PURPLE BOUNDARY PAINT

(Contd. of page 2)

**1330-20-7 xylene (mix)**

BEI (USA)	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
-----------	--

**Hygienic protection:** Immediately remove all soiled and contaminated clothing.  
Wash hands after use.

Avoid contact with the eyes and skin.  
Do not eat or drink while working.

**Breathing equipment:** A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.

**Hand protection:** Nitrile gloves.

Protective gloves. The glove material must be impermeable and resistant to the substance.  
Tightly sealed goggles

**Eye protection:**

**9 Physical and chemical properties**

**Appearance:** Aerosol.

**Odor:** Aromatic

**Odor threshold:** Not determined.

**pH-value:** Not determined.

**Melting point/Melting range** Undetermined.

**Boiling point:** -44 °C (-47 °F)

**Flash point:** -19 °C (-2 °F)

**Flammability (solid, gas):** Extremely flammable.

**Decomposition temperature:** Not determined.

**Auto igniting:** Product is not self-igniting.

**Danger of explosion:** In use, may form flammable/explosive vapour-air mixture.

**Lower Explosion Limit:** 1.7 Vol %

**Upper Explosion Limit:** 44.0 Vol %

**Vapor pressure:** Not determined.

**Relative Density:** Between 0.77 and 0.85 (Water equals 1.00)

**Vapor density** Not determined.

**Evaporation rate** Not applicable.

**Partition coefficient: n-octanol/water:** Not determined.

**Solubility:** Not determined.

**Viscosity:** Not determined.

**VOC content (less exempt solvents):** 56.0 %

**Solids content:** 30.4 %

**10 Stability and reactivity**

**Reactivity:** Stable at normal temperatures.

**Conditions to avoid:** Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing temperatures.

**Chemical stability:** Not fully evaluated.

**Possibility of hazardous reactions:** No dangerous reactions known.

**Incompatible materials:** No further relevant information available.

**Hazardous decomposition:** No dangerous decomposition products known.

**11 Toxicological information****LD/LC50 values that are relevant for classification:****67-56-1 methanol**

Oral	LD50	13000 mg/kg (rat)
------	------	-------------------

**106-97-8 n-butane**

Inhalative	LC50/4 h	658 mg/l (rat)
------------	----------	----------------

**13463-67-7 titanium dioxide**

Oral	LD50	>20000 mg/kg (rat)
------	------	--------------------

Dermal	LD50	>10000 mg/kg (rbt)
--------	------	--------------------

Inhalative	LC50/4 h	>6.82 mg/l (rat)
------------	----------	------------------

**108-65-6 PM acetate**

Oral	LD50	8500 mg/kg (rat)
------	------	------------------

Inhalative	LC50/4 h	35.7 mg/l (rat)
------------	----------	-----------------

**1330-20-7 xylene (mix)**

Oral	LD50	8700 mg/kg (rat)
------	------	------------------

Dermal	LD50	2000 mg/kg (rbt)
--------	------	------------------

Inhalative	LC50/4 h	6350 mg/l (rat)
------------	----------	-----------------

**Information on toxicological effects:** No data available.

**Skin effects:** No irritant effect.

**Eye effects:** Irritating effect.

(Contd. on page 4)

## Safety Data Sheet

Printing date 02/14/2017

Revised On 02/14/2017

Trade name: PURPLE BOUNDARY PAINT

Sensitization: No sensitizing effects known.

(Contd. of page 3)

## 12 Ecological information

**Aquatic toxicity:** Hazardous for water, do not empty into drains.  
**Persistence and degradability:** The product is degradable after prolonged exposure to natural weathering processes.  
**Bioaccumulative potential:** No further relevant information available.  
**Mobility in soil:** No further relevant information available.  
**Other adverse effects:** No further relevant information available.

## 13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.  
**Recommendation:** Completely empty cans should be recycled.

## 14 Transport information

**UN-Number** UN1950  
**DOT** N/A  
**DOT** Consumer Commodity ORM-D  
**ADR** Aerosols, flammable  
**Transport hazard class(es):** 1950 Aerosols  
**Class** 2.1  
**Special precautions for user:** Warning: Gases  
**EMS Number:** F-D,S-U  
**Stowage Code** SW1 Protected from sources of heat.  
 SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.  
**Segregation Code** SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.  
**Quantity limitations** On passenger aircraft/rail: 75 kg  
 On cargo aircraft only: 150 kg

---

**ADR**  
**Excepted quantities (EQ)** Code: E0  
 Not permitted as Excepted Quantity

---

**IMDG**

**Limited quantities (LQ)** 1L  
**Excepted quantities (EQ)** Code: E0  
 Not permitted as Excepted Quantity

**Packaging Group:** --  
**UN "Model Regulation":** UN 1950 AEROSOLS, 2.1

## 15 Regulatory information

**SARA Section 355 (extremely hazardous substances):**

None of the ingredients in this product are listed.

**SARA Section 313 (Specific toxic chemical listings):**

67-56-1	methanol
1330-20-7	xylene (mix)

**TSCA:** All ingredients are listed.  
**CPSC:** This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

**California Proposition 65 chemicals known to cause cancer:**

13463-67-7	titanium dioxide
100-41-4	ethyl benzene

**California Proposition 65 chemicals known to cause birth defects or reproductive harm:**

67-56-1 Methanol

None of the ingredients in this product are listed.

**CANADIAN ENVIRONMENTAL PROTECTION ACT:****WHMIS Symbols for Canada:**

All hazardous ingredients for this product appear on the Canadian Domestic Substance List.  
 A - Compressed gas  
 D2B - Toxic material causing other toxic effects

**EPA:**

67-64-1	Acetone	I
1330-20-7	xylene (mix)	I

## 16 Other information

Contact: Regulatory Affairs

(Contd. on page 5)

**Safety Data Sheet**

Printing date 02/14/2017

Revised On 02/14/2017

**Trade name: PURPLE BOUNDARY PAINT****Date of preparation / last revision** 02/14/2017 / -

(Contd. of page 4)